

Superflat Reinforced PVC Hose

LX series



Green - Garden & Car Wash



Blue - Camping, Boating & Caravanning



Economy Fittings



Deluxe Fittings

Coplexel

General Description

Coplexel Superflat hoses were developed from their industrial origins to provide a unique water hose which stores in a small space, drains easily and can be equipped with its own cassette. The Superflat hose achieved a Design Centre selection.

Codeflex Superflat is manufactured from a special formulation of PVC containing low temperature stabilisers and anti-scuffing agents, reinforced with high tensile polyester fibre. This process results in a hose extremely light in weight, but able to withstand pressure well in excess of normal domestic water pressure. Superflat assumes a conventional round appearance under pressure, and its memory for a flat profile ensures self-draining after use. Superflat can be left outdoors in all weathers and will give many years of useful service. Superflat comes complete with a fully functional FREEWHEELER cassette offering compact storage and ease of use, with a choice of either Deluxe Quick Release or Economy Tap Connector and Spray Nozzle.

Coplexel Marine Superflat reinforced PVC water hose with natural low toxic inner to F & D.A.**approved material. Opaque blue outer wound on cassette / winder with 20 metres of hose.

The regulations specifically ensure that the compounds are cadmium free. (Copely were perhaps the first to have a Cadmium free specification some 10 years ago).

This hose is not designed for permanent water installation, please see Codeflex Aquavend for WRAS approved mains hose.

Hose construction manufactured from F & DA/low toxic PVC raw materials.

Technical Data

UK and European Sizes

Product Ref	Size I.D.	Weight per coil kgs	Working Pressure Bar
LX 12	1/2" (12mm)	1.35	8.5
LX 16	5/8" (16mm)	1.9	8.5

Available in 10m, 15m and 20m coils.

Casseted Superflat

LX 12/15	15 metre hose on white cassette
LX 12/20	20 metre hose on white cassette

The above can be supplied with two types of fittings:

- 1) Deluxe, quick release couplings
- 2) Economy tap connection and spray nozzle.

Please indicate preferences when ordering.

Marine Superflat

Product Ref	Size I.D.	Weight per coil kgs	Working Pressure Bar
LX 12/20/WFQ	1/2"	2.2	8.5

UK Standard Stock Sizes in 20m coils.

Complete with quick release fittings - Universal tap connector and adjustable spray nozzle.

Each unit supplied with header card and shrink wrapped.

LX 12/20/WFE	1/2"	2.2	8.5
--------------	------	-----	-----

Complete with economy fittings - Universal tap connector.

Resistant Methods & Procedures:

- BS 6596: 1992
- ISO 7751: 1991
- ISO 1402: 1994
- BS EN 24671: 1993

Please see Standards Index for further information

Special Features

Food

■ Made from Cadmium free materials

Abrasive

■ Silicone free

Water

■ Unique manufacturing process

Chemicals

■ High Flexibility

■ Can be equipped with own cassette

■ Drains easily

■ Unique compact water hose

Note:

Food and Drink Marine only